



EDK2B-LED

Both contactless media and contact chips reader with double-digit LED display. Terminal is used mainly in catering systems – shows the number of issued meal or distribution point.

In commuting system, it displays current tariff of fare, apart from reading ID media. Fitted using supplied holder.

Product Code	Description
EDK2-LED	Contact DALLAS Chips reader with display
EKD2B-LED	Contactless Reader with display

TECHNICAL SPECIFICATION

Type designation	EDK2-LED	EDK2B-LED
Power Supply	DC 10 - 30V (typ. 12V)	DC 10 - 30V (typ. 12V)
Input current	Max 150 mA (@12V DC)	Max 150 mA (@12V DC)
ID media	dallas	contactless
Size	110 x 33 mm	110 x 33 mm
Casing	IP 40	IP 40
Weight	130 g	130 g
Working temperature	-20 °C až +50 °C	-20 °C až +50 °C
Storage temperature	-40 °C až +65 °C	-40 °C až +65 °C
Indication	LED, PIEZO	LED, PIEZO
Montage	Partially sunk into the wall	



**ELECTRONIC
IDENTIFICATION
SYSTEM**

Producer: ESTELAR s. r. o.
Samostatnost 1181, 769 01 Holešov, Czech Republic
phone: +420 573 394 894, e-mail: sales@estelar.cz

www.acsline.com